290428US3PCT

10/577651

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF:

Hisashi MATSUDA, et al.

IAP20 Rec'd PCTAPTO 01 MAY 2006

SERIAL NO: New U.S. PCT Application Based on PCT/JP04/16461

GAU:

FILED:

Herewith

EXAMINER:

FOR:

TURBINE CASCADE STRUCTURE

INFORMATION DISCLOSURE STATEMENT UNDER 37 CFR 1.97

COMMISSIONER FOR PATENTS ALEXANDRIA, VIRGINIA 22313

SIR:

Applicant(s) wish to disclose the following information.

REFERENCES

	The applicant(s) wish to make of record the references listed on the attached form PTO-1449. Copies of the listed
_	references are attached, where required, as are either statements of relevancy or any readily available English
	translations of pertinent portions of any non-English language references.

☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

RELATED CASES

Attached is a list of applicant's pending application(s), published application(s) or issued patent(s) which may be
 related to the present application. In accordance with the waiver of 37 CFR 1.98 dated September 21, 2004, copies
of the cited pending applications are not provided. Cited published and/or issued patents, if any, are listed on the
attached PTO form 1449.

☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

CERTIFICATION

	Each item of information contained in this information disclosure statement was first cited in any communication
_	from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of
	this statement.

No item of information contained in this information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application or, to the knowledge of the undersigned, having made reasonable inquiry, was known to any individual designated in 37 CFR §1.56(c) more than three months prior to the filing of this statement.

DEPOSIT ACCOUNT

Please charge any additional fees for the papers being filed herewith and for which no check or credit card payment is enclosed herewith, or credit any overpayment to deposit account number 15-0030. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND, MAIER & NEUSTADT, P.C.

C. Irvin McClelland

Registration No. 21,124

22850

Customer Number

Tel. (703) 413-3000

Fax. (703) 413-2220

(OSMMN 05/03)

Surinder Sachar

Registration No. 34,423

JAP20Rec'd PCT/PTO 01 MAY 2006

SHEET 1 OF 1

Form PTO 1449 U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE			ATTY DOCKET NO. 290428US3PCT SERIAL NO. NEW D.S. P.O. Application Based on PCT/JP04/16461					
				APPLICANT Based on PCT/JP04/16461				
LIST OF	REFE	RENCES CITED BY A	APPLICANT	Hisashi MATSUDA, et al.				
				FILING DATE	<u> </u>	GROUP		
				Herewith		311001		
	_			U.S. PATENT DOCUMENTS		l .		
EXAMINER INITIAL		DOCUMENT NUMBER	DATE	NAME	CLASS	SUB CLASS	FILING DATE IF APPROPRIATE	
	AA	6 419 446	07/16/02	KVASNAK et al.				
	AB							
	AC							
	AD							
	AE							
	AF							
	AG							
	АН							
	Al							
	AJ							
	AK							
	AL							
	АМ							
	AN							
			FO	REIGN PATENT DOCUMENTS				
	DOCUMENT DATE			COUNTRY		TRANSLATION YES NO		
	AO	62-3847	01/09/87	JP (equivalent of US4704066)			NO	
	AP	5-44691	02/23/93	JP			NO	
	AQ	55-142909	11/07/80	JP			NO	
	AR	73304/1982	05/06/82	JP			NO	
_	AS	63503/1988	4/26/88	JP			NO	
	AT	61-252838	11/10/86	JP (equivalent of US4709546)			NO	
	AU	1-237305	09/21/89	JP		_	NO	
	AV	4-78803	12/14/92	JP			NO	
7	AW	4-124406	04/24/92	JP			NO	
	AX	9-112203	04/28/97	JP			NO	
	AY	2000-230403	08/22/00	JP			NO	
		OTHER F	REFERENCES (Including Author, Title, Date, Pertinen	t Pages, el	tc.)		
	AZ		ndary-Flow Structure by Leading-Edge Aerodynamic Loss and Surface Heat bo Expo, 2002.					
Examiner					Date Considered			
				t citation is in conformance with MPEP 60 with next communication to applicant.	D9; Draw lir	ne through	citation if not in	

New U.S. PCT Application Based on PCT/JP04/16461 Hisashi MATSUDA, et al. Docket No. 290428 US

STATEMENT OF RELEVANCY

- 1) References AO AU have been cited in the International Search Report. A copy of these references is being submitted herewith.
- 2) References have been cited in the corresponding Search Report. A copy of these references is being submitted herewith.
- 3) References AA, AV AY & AZ are discussed in the specification. A copy of these references is being submitted herewith.
- 4) References are additional prior art known to Applicant. A copy of these references is being submitted herewith.

AV: JP4-78803

This discloses a turbine nozzle preventing secondary flow by suppressing a boundary layer caused at an annular flow peripheral wall surface of the turbine nozzle, and also preventing the secondary flow loss by the secondary vortex to thereby improve the turbine performance. In this invention, the turbine nozzle has a structure satisfied by an equation determined by the nozzle blade height, inclinations of rear edge lines at the intermediate portion of the nozzle blade with respect to a reference line passing the rotation center of the turbine, and heights of the rear edge lines.

AW: JP4-124406

This discloses a stationary blade device of an axial flow turbine, in which a front edge portion and a rear edge portion of the stationary blade have equal curved inclination angles in an expansion flow direction of an expanded fluid to thereby reduce the secondary flow loss.

AX: JP9-112203

This discloses a turbine nozzle for reducing the secondary flow loss by controlling turbine nozzle flow line and flow distribution with inclination of the nozzle and throat width(S)/annular pitch (T) distribution to thereby improve turbine stage performance, in which the ration of S/T is determined by a specified equation at the root portion, central portion and front portion of the turbine nozzle.

AY: JP2000-230403

This discloses an axial flow rotating machine such as a stationary blade of a turbine for guiding working fluid, in which a protruded staged portion is formed to a rear surface side, i.e. suction side, of the blade toward blade height direction from a chip side and hub side to thereby reduce a secondary loss of the turbine blade.